

MICRO SERIES PRODUCT SPECS:



PRODUCT NAME — Guardian Angel™ Micro™ Series LED Light Bar

LIGHT SOURCE — 11 LEDs

COLORS — Red, White, Yellow, Green, Orange, Infrared

BRIGHTNESS — Up to 500 lumens (varies by model),
3+ Miles Visibility

SIZE — 1.99"W x 1.72"L x 0.68"H

WEIGHT — 2.0 oz, 56.70g

BATTERY — **Type:** Rechargeable Lithium Polymer Battery
Capacity: 700mAh / 1.85Wh
Charging Time: Approx. 50 minutes
Normal Voltage: 3.7V
Certification: UN38.3, IEC62133, CE, RoHS Compliant
Battery Life hr/charge: Varies based on
brightness setting & light mode. 2 – 150 hours
Battery Life Cycle: 3,000 cycles minimum

CHARGING — **Connector:** Type C USB
Input: AC 100-240V - 50/60Hz. 0.6A
Output: 5.0V - 1000mA

CASING — **Material:** Polycarbonate Lens, Glass Filled
Polycarbonate Exterior Covers and USB Door,
High Temperature Rubber Buttons & Water Seals
IP Rating: IP67 Water/Dust Proof Rating
Flammability Rating: UL 746B, UL94

MOUNTING — Neodymium iron boron Grade NB42 magnets

ENVIRONMENT — **Operational Temp & Humidity:** -40C°- 110C°
Storage Temp & Humidity: 20-28C°

TETHER ATTACHMENT

Tether Accessory Attachment

GA EMERGENCY MODE

- 1st Press= All LEDs Flashing
- 2nd Press= OFF
- Hold= Scrolling Sequence (Push Again to Turn Off)

BRIGHTNESS SETTINGS

Max, High, Medium, Low or SOS Light Pattern

REAR LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold= Battery Level Indicator

CHARGING PORT

Rechargeable
Type-C USB
Charging Port
(on side)

DURABLE

Waterproof, Dustproof,
Shockproof, IP67 Rated

WORK LIGHT

- 1st Press= Single LED On
- 2nd Press= OFF
- Hold= Standard Operating Mode (All Front LED's On, Rear LED's Flashing)

BUILT IN MAGNET

Super Strong Built-in Rare Earth Magnet Mounting System (on underside)

FRONT LED'S

- 1st Press= Constant On
- 2nd Press= Constant Blinking
- 3rd Press= Scrolling Sequence
- 4th Press= OFF
- Hold On/Off = For Top LED

